



**PITTSBURGH**  
*Proof* Products

**WATERSPAR**  
QUICK  DRYING  
REG. U.S. PAT. OFF.  
**VARNISH**

+PITTSBURGH+  
PLATE GLASS CO.  
PAINT-VARNISH-LACQUER



E. J. White Paint & Glass Co.,  
123 St. Paul Street,  
Burlington, Vt.

# WATERSPAR QUICK DRYING VARNISH

*Now old surfaces can be revarnished and placed back in use after 4 hours.*

The varnishes in this line were developed principally for renewing old surfaces without necessitating the removing of the old finish. The colored varnishes stain and varnish in one application.

The colors are the result of adding high grade transparent coloring matter and other necessary ingredients to clear Waterspar Quick Drying Varnish.

This varnish dries in 4 hours under normal conditions and permits the application of two coats within one day.

The finish is semi-transparent. The colors are suitable for all interior household use.

Apply to floors, woodwork, furniture, etc. Use same as other high grade finishing varnishes. Where added durability is desired, apply three coats, sanding lightly between coats with fine sandpaper, and always dust thoroughly.

The Gold and Aluminum produce a high grade, hard, washable ENAMEL FINISH that is not affected by heat nor cold.

Suitable for use on Bedsteads, Bric-a-Brac, Engines, Frescowork, Furniture, Gas Fixtures, Mouldings, Ornaments, Picture Frames, Plumbing, Radiators, Stoves, Statuary, etc.



83-101  
LIGHT OAK



83-102  
DARK OAK



83-103  
WALNUT



83-104  
DARK MAHOGANY



83-113  
GOLD



83-114  
ALUMINUM

Also 83-100 Clear Interior, 54-108 Ground Color and 83-200 Transparent for Exterior Use.

## DIRECTIONS

Stir contents thoroughly from the bottom. The surface to be finished must be thoroughly cleaned and free from all dirt, wax and grease. Use turpentine for removing wax and grease. For application of Waterspar Quick Drying Colored Varnish, the Fulton Varnish Brush, made by the Pittsburgh Plate Glass Company, is especially recommended. One coat of Clear or Colored Waterspar Quick Drying Varnish is generally sufficient to brighten up the surface. Two coats will produce a higher luster. If surface is stained or discolored, or if it is desired to change the color, proceed as follows:

**FIRST COAT**—Apply a coat of three parts of Waterspar Quick Drying Ground Color and one part of Waterspar Quick Drying Varnish of the color desired. Allow from four to six hours for drying.

**FINISHING COAT**—Finish with one or more coats of Waterspar Quick Drying Varnish of color desired. New or previously unvarnished surfaces should be given two coats of Waterspar Quick Drying Varnish of color desired, reducing first coat with one-quarter gallon of turpentine to the gallon of varnish. Sand entire surface lightly, dusting carefully before applying finishing coat.

**CAUTION:**—Keep Paint, Varnish and Lacquer Away from Fire.

Successful painting requires the use of a proper brush, **use a Gold Stripe Brush.**